

Video & TV Generators

Selection Guide

	PM 5414V	54100	PM 5415	PM 5418	54200
TV systems	PAL NTSC	PAL NTSC SECAM	PAL NTSC SECAM	PAL NTSC SECAM	PAL NTSC SECAM
Teletext and data systems		UK TXT Antiope Closed Caption PDC VPS WSS	UK TXT Antiope Closed Caption PDC VPS	UK TXT Antiope Closed Caption PDC VPS	UK TXT Antiope Closed Caption PDC VPS WSS
Video Signals Outputs	CVBS Y/C RGB	CVBS Y/C YCrCb RGB	CVBS Y/C RGB	CVBS Y/C RGB	CVBS Y/C YCrCb RGB
RF Output	--	--	Yes	Yes	Yes
Frequency Range	--	--	32...900 MHz, $\Delta f = 250$ kHz	32...900 MHz, $\Delta f = 250$ kHz	32...900 MHz, $\Delta f = 50$ kHz
Output Level and attenuation	--	--	10 mV max, 0...60 dB	10 mV max, 0...60 dB	100 mV max, 0...80 dB
Sound systems	--	--	Mono, German stereo, NICAM, BTSC	Mono, German stereo, NICAM, BTSC	Mono, German stereo, NICAM, BTSC, Korean stereo, FM A2 stereo
Remote control	--	Optional	--	Optional	Optional
Interface		IEEE-488.2 RS-232		IEEE-488.1	IEEE-488.2 RS-232
Functions		Full remote control		Limited remote control	Full remote control

Note: The functionality as indicated above may not be available in all versions of the main typenumbers given. Refer to the individual product pages for full details on functionality and models available.